



RPM	MODELLO MODEL	PORTATA FLOW		PRESSIONE PRESSURE		POTENZA POWER		PESO WEIGHT	
		l/min	GPM	bar	PSI	HP	kW		
1450	★★★ PNC 04/10 S	4.0	1.1	100	1450	1.0	0.7	5.3	S = Albero Maschio 24 mm S = Male Shaft 24 mm
	★★★ PNC 06/10 S	6.0	1.6	100	1450	1.5	1.1	5.3	
	PNC 09/11 S	9.0	2.4	110	1595	2.5	1.9	5.3	I = Albero cavo 28 mm (con Flangia P07) I = Hollow Shaft 28 mm (with Flange P07)
	PNC 09/17 S	9.0	2.4	170	2465	3.9	2.9	5.6	
	PNC 11/11 S	11.0	2.9	110	1595	3.1	2.3	5.3	
	PNC 12/14 I	12.0	3.2	140	2030	4.3	3.2	5.7	
	PNC 13/12 S	13.0	3.4	120	1740	4.0	2.9	5.3	
PNC 13/15 S	13.0	3.4	150	2175	5.0	3.7	5.6		
1750	PND 2.0/20 S	7.6	2.0	140	2030	2.7	2.0	5.3	S = Albero Maschio 24 mm S = Male Shaft 24 mm
	PND 2.0/20 Z	7.6	2.0	140	2030	2.7	2.0	5.7	
	PND 3.0/20 S	11.4	3.0	140	2030	4.1	3.0	5.3	Z = Albero Cavo 5/8" (con Flangia P03) Z = Hollow Shaft 5/8" (with Flange P03)
	PND 3.0/20 Z	11.4	3.0	140	2030	4.1	3.0	5.7	
	PND 3.5/20 S	13.2	3.5	140	2030	4.7	3.5	5.3	
	PND 3.5/20 Z	13.2	3.5	140	2030	4.7	3.5	5.7	
	PND 4.0/20 S	15.0	4.0	140	2030	5.4	4.0	5.3	
PND 4.0/20 Z	15.0	4.0	140	2030	5.4	4.0	5.7		
2800	PNE 08/14 S	8.0	2.1	140	2030	2.9	2.1	5.3	S = Albero Maschio 24 mm S = Male Shaft 24 mm
	PNE 11/14 S	11.0	2.9	140	2030	3.9	2.9	5.3	
	PNE 13/12 S	13.0	3.4	120	1740	4.0	2.9	5.3	
	PNE 13/15 S	13.0	3.4	150	2175	5.0	3.7	5.6	
3400	PNL 2.5/20 T	9.5	2.5	140	2030	3.4	2.5	5.6	T = Albero Cavo 3/4" (con Flangia P01) T = Hollow Shaft 3/4" (with Flange P01)
	PNL 3.0/20 T	11.4	3.0	140	2030	4.1	3.0	5.6	
	PNL 3.0/25 T	11.4	3.0	170	2465	5.0	3.7	6.0	
	PNL 3.5/22 T	13.2	3.5	150	2175	5.1	3.7	6.0	

★★★ FOR MISTING

Vedi pag. 38 - See pag. 38